
Abrasive film, self-fastening, waterproof

FP 77 K T-ACT





Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Semi-open
Backing	Film

Product benefit

New high-performance disc with optimized clogging behaviour - Increased service life due to the new coating, which prevents the adhesion of paint and dust particles - For fine sanding in the fine grit range 240 - 2000, a highly flexible and completely flat film backing is used for highest surface quality

Materials

Paint/Varnish/Filler	●
Primer	●
Filler	●
Gel coats	●
Composite materials	●
Plastic	●

Applications

- Automotive industry
- Boat and shipbuilding
- Wind energy industry
- Furniture industry

Available grits:

16 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter in mm	grain	Hole pattern	type of coat.abras.	Packing unit/pcs.	Cat. number
125	240	◯ 0	FP 77 K	100	353177
125	320	◯ 0	FP 77 K	100	353175

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter in mm	grain	Hole pattern	type of coat.abras.	Packing unit/pcs.	Cat. number
125	400	◯ 0	FP 77 K	100	353174
125	600	◯ 0	FP 77 K	100	353172
125	240	GLS 5	FP 77 K	100	353162
125	280	GLS 5	FP 77 K	100	353161
125	320	GLS 5	FP 77 K	100	353169
125	400	GLS 5	FP 77 K	100	353160
125	600	GLS 5	FP 77 K	100	353158
150	240	GLS 3	FP 77 K	100	353146
150	320	GLS 3	FP 77 K	100	353145
150	400	GLS 3	FP 77 K	100	353144
150	600	GLS 3	FP 77 K	100	353142
150	800	GLS 47	FP 77 K	100	353134
150	1000	GLS 47	FP 77 K	100	353133
150	1200	GLS 47	FP 77 K	100	353132
150	1500	GLS 47	FP 77 K	100	353131
150	2000	GLS 47	FP 77 K	100	353130

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de