

Sandflex mottling points

SFM 656



Properties

Bonding agent	Plastic
Grain	SiC

Product benefit

Produces a glossy finish on stainless steel surfaces - Soft abrasion due to elastic structure - Can be used until completely worn down - Available in two executions: with flattened shaft for simple and secure clamping (standard execution, stock items) and with full length round shaft (made to order items)

Materials

Stainless steel ●

Applications

► Apparatus and container manufacturing

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Diameter x Height x Shaft in mm	grain	Bond	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
50 x 30 x 6	60	W	5 m/s	1900 rpm	10	13862
50 x 30 x 6	120	W	5 m/s	1900 rpm	10	13863

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

