Cutting-off wheel

A 36 TZ SPECIAL





Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■□
Aggression	■■■■■■■
Service life	■■■■■□□

Product benefit

Very good cutting performance, even with low grinding pressure

Materials

Stainless steel	●
Steel	◑

Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop
- Stainless steel processing industry
- Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 2 x 22,23	▬▬	80 m/s	13300 rpm	25	136549
125 x 2 x 22,23	▬▬	80 m/s	12200 rpm	25	136550
180 x 2 x 22,23	▬▬	80 m/s	8500 rpm	25	136551
230 x 2 x 22,23	▬▬	80 m/s	6600 rpm	25	136552

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de