Cutting-off wheel

A 630 N *SUPRA*



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■■■□
Service life	■■■■■■□

Materials

Steel	●
Stainless steel	◑
Aluminium	◑
Castings	◑

Product benefit

Aggressive model with an outstanding service life - An exceptional choice for the cutting of solid material - Bond optimized for universal use - Low thermal load - Minimum burr formation

Applications

- Plant engineering
- Apparatus and container manufacturing
- Locksmith's shop
- Steel construction
- Road building
- Construction above and below ground

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
300 x 2,5 x 25,4	▬▬	80 m/s	5100 rpm	10	353325
356 x 2,5 x 25,4	▬▬	80 m/s	4400 rpm	10	353324
406 x 3,2 x 25,4	▬▬	80 m/s	3800 rpm	10	353328

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de